



GADREN GADE™ HEAVY-DUTY VALVES

HEAVY DUTY FOR INDUSTRIAL AND COMMERCIAL USE

GADE HEAVY-DUTY VALVES ARE USED FOR RELIABLE CONTROL OF LIQUIDS IN OPEN OR CLOSED TANKS, RESERVOIRS, COOLING TOWERS, VATS OR ANY APPLICATION WHERE RELIABILITY IS A MUST. ALL GADE VALVES ARE BALANCED FOR EASY OPERATION AT A HIGHER PRESSURE. THIS BALANCED ACTION ALSO PROVIDES EASIER OPENING AND CLOSING TO SAVE WEAR AND TEAR ON THE VALVE AND PROVIDE A TIGHT CLOSING SEAL ON THE SINGLE SURFACE. OUR VALVES ARE AVAILABLE IN EITHER ANGLED-BODIED OR STRAIGHT-THROUGH CONFIGURATIONS WITH EITHER THE STANDARD NEOPRENE DISK AND LEATHER CUP OR WITH OPTIONAL TEFLON® CUP DISC. GADE VALVES ARE ALSO AVAILABLE IN EITHER BRONZE OR TYPE 316 STAINLESS STEEL IN SIZES FROM 1/2" TO 3" NPT.

KEY FEATURES

- SIZES 1/2" TO 3" NPT
- AVAILABLE IN BRONZE OR 316 STAINLESS STEEL
- NEOPRENE DISC FOR UP TO 180° OR A TEFLON® DISC FOR HOT WATER AND CHEMICAL APPLICATIONS
- ADJUSTABLE SWIVEL AND FLOAT ROD LEVEL
- REVERSIBLE ACTION
- AVAILABLE WITH STUFFING BOX AND EXTERNAL MOUNTING
- BALANCED ACTION: SINGLE SEATED FOR TIGHT CLOSING
- MADE IN USA

CONSTRUCTION: BRASS OR STAINLESS STEEL

SEALS

COLD - NEOPRENE AND LEATHER
HOT - TEFLON

CODE OF VALVES

- A- ANGLED BODY TYPE
- G- GLOBE BODY TYPE
- C- COLD WATER SERVICE
- H- HOT WATER SERVICE
- F- FLOAT OPERATED
- L- LEVER OPERATED
- B- STUFFING BOX

FLOAT VALVES

GADREN GADE™ HEAVY-DUTY VALVES

GADE™ HEAVY-DUTY BRASS FLOAT VALVE

Body Type	Model	Inlet	Outlet	Float Ball	Stem (in)	Max Inlet Pressure	55 PSI
Angle	ACF AHF	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM
Globe	GCF GHF	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM



GADE™ HEAVY-DUTY STAINLESS STEEL FLOAT VALVE

Body Type	Model	Inlet	Outlet	Float Ball	Stem (in)	Max Inlet Pressure	55 PSI
Angle	AHFSS	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM
Globe	GHFSS	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM



GADE™ HEAVY-DUTY LEVER-OPERATED FLOAT VALVE

Body Type	Model	Inlet	Outlet	Float Ball	Stem (in)	Max Inlet Pressure	55 PSI
Angle	ACLB AHLB AHLBSS	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM
Globe	GCLB GHLB GHLBSS	1/2"	1/2"	5"	1/4" IPS X 16"	100	30 GPM
		3/4"	3/4"	5"	1/4" IPS X 16"	100	50 GPM
		1"	1"	6"	1/4" IPS X 18"	100	75 GPM
		1 1/2"	1 1/2"	6"	1/4" IPS X 18"	100	125 GPM
		2"	2"	8"	3/8" IPS X 20"	100	175 GPM
		3"	3"	8"	3/8" IPS X 24"	100	400 GPM



FOR EXTERNAL OPERATING USE